



- **Full steel construction** extremely robust to perforation
- Optimum protection of grass sward and crops by rounded shoulders
- Excellent lateral grip by special block design with multi oriented faces
- Limited stone and mud retention due to optimum tread geometry
- Excellent directional stability due nearly continuous central rib & tread stiffness

### Technical data

Load index   speed symbol	167D	Type	TL
Diameter (mm)	1485	Width (mm)	727
Tread depth (mm)	23	Rim	24.00 x 30.5
Static load radius (mm)	668	Rolling circumference (mm)	4500

### Load capacity per tire (kg) according to ETRTO\* | Inflation pressure

Bar	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
10 km/h	4025	5005	5690	6575	7460	8145	8930	9810
25 km/h	3535	4395	5000	5775	6550	7155	7840	8615
40 km/h	3045	3785	4305	4970	5640	6155	6750	7415
50 km/h	2705	3365	3830	4420	5015	5475	6005	6595
65 km/h	2235	2780	3165	3655	4145	4525	4960	5450

\* check load capacity rim



**FLOTXTRA**



**DE MOLEN**  
BANDEN

RUSTVENSEWEG 2 - 5375KW - REEK  
TEL: 0486-479727  
WWW.DEMOLENBANDEN.NL