



MAXAM

MS961R

FLOTXTRA

- **SOIL PROTECTION** - Optimum protection of grass sward and crops by rounded tread lug edges. Low soil compaction by wide tread lugs construction and better pressure distribution in the footprint due to tread stiffness
- **LATERAL STABILITY**- Excellent lateral grip by special block design with multi oriented faces combined with excellent self-cleaning properties
- **DURABILITY & MILEAGE** - Full steel construction extremely robust to perforation. Excellent mileage performance thanks to special rubber compound
- **SAFETY** - Limited stone and mud retention due to optimum tread geometry. Excellent directional stability due nearly continuous central rib and tread stiffness

Applications



Size	LI/SS	Type	Rim Recommended	Section Width	Overall Diameter	Static Loaded Radius	Rolling Circumference	Speed Radius Index
* Available mid 2017			inch	mm	mm	mm	mm	
600/50R22.5 IMP	159 D	TL	AG20.00x22.5	611	1172	527	3550	550
500/60R22.5 IMP	155 D	TL	AG16.00x22.5	503	1172	527	3550	550
560/60R22.5 IMP	161 D	TL	AG16.00x22.5	543	1244	560	3770	600
560/45R22.5 IMP	152 D	TL	AG16.00x22.5	543	1076	484	3260	525
710/40R22.5 IMP	161 D	TL	AG24.00x22.5	727	1140	513	3455	550
600/55R26.5 IMP	165 D	TL	AG20.00x26.5	611	1333	600	4040	625
650/55R26.5 IMP	169 D	TL	AG20.00x26.5	645	1389	625	4210	650
710/50R26.5 IMP	170 D	TL	AG24.00x26.5	727	1383	622	4190	650
800/45R26.5 IMP *	174 D	TL	AG28.00x26.5	828	1393	627	4220	675
650/65R30.5 IMP *	176 D	TL	AG20.00x30.5	645	1621	729	4910	775
710/50R30.5 IMP *	173 D	TL	AG24.00x30.5	727	1485	668	4500	700
750/60R30.5 IMP *	181 D	TL	AG24.00x30.5	754	1675	754	5075	800

