



- **Full steel construction** extremely robust to perforation
- Optimum protection of grass sward and crops by rounded shoulders
- Excellent lateral grip by special block design with multi oriented faces
- Limited stone and mud retention due to optimum tread geometry
- Excellent directional stability due nearly continuous central rib & tread stiffness

### Technical data

Load index   speed symbol	155D	Type	TL
Diameter (mm)	1172	Width (mm)	503
Tread depth (mm)	18	Rim	16.00 x 22.5
Static load radius (mm)	503	Rolling circumference (mm)	3550

### Load capacity per tire (kg) according to ETRTO\* | Inflation pressure

Bar	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
10 km/h	2930	3490	4120	4710	5235	5860	6420	6975
25 km/h	2575	3065	3615	4135	4595	5145	5635	6125
40 km/h	2215	2635	3110	3560	3955	4430	4850	5270
50 km/h	1970	2345	2770	3170	3520	3940	4315	4690
65 km/h	1630	1940	2290	2620	2910	3255	3565	3875

\* check load capacity rim



**FLOTXTRA**



**DE MOLEN**  
BANDEN

RUSTVENSEWEG 2 - 5375KW - REEK  
TEL: 0486-479727  
WWW.DEMOLENBANDEN.NL