



- **Full steel construction** extremely robust to perforation
- Optimum protection of grass sward and crops by rounded shoulders
- Excellent lateral grip by special block design with multi oriented faces
- Limited stone and mud retention due to optimum tread geometry
- Excellent directional stability due nearly continuous central rib & tread stiffness

#### Technical data

Load index   speed symbol	161D	Type	TL
Diameter (mm)	1244	Width (mm)	543
Tread depth (mm)	18	Rim	16.00 x 22.5
Static load radius (mm)	560	Rolling circumference (mm)	3770

#### Load capacity per tire (kg) according to ETRTO\* | Inflation pressure

Bar	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.2	3.6	4.0
10km/h	3780	4200	4620	5050	5470	5900	6320	6750	7050	7230	7600	7960	8330
25 km/h	3190	3580	3970	4360	4750	5140	5530	5910	6190	6350	6670	6990	7310
40km/h	2790	3120	3450	3770	4100	4430	4760	5090	5330	5460	5740	6010	6290
50 km/h	2470	2760	3060	3350	3650	3940	4240	4530	4740	4860	5110	5350	5600
65 km/h	2070	2310	2550	2790	3030	3270	3510	3750	3920	4020	4220	4420	4630

\* check load capacity of rim



**FLOTXTRA**



**DE MOLEN**  
BANDEN

RUSTVENSEWEG 2 - 5375KW - REEK  
TEL: 0486-479727  
WWW.DEMOLENBANDEN.NL