



- **Full steel construction** extremely robust to perforation
- Optimum protection of grass sward and crops by rounded shoulders
- Excellent lateral grip by special block design with multi oriented faces
- Limited stone and mud retention due to optimum tread geometry
- Excellent directional stability due nearly continuous central rib & tread stiffness

Technical data

Load index speed symbol	159D	Type	TL
Diameter (mm)	1168	Width (mm)	592
Tread depth (mm)	18	Rim	20.00 x 22.5
Static load radius (mm)	521	Rolling circumference (mm)	3592

Load capacity per tire (kg) according to ETRTO* | Inflation pressure

Bar	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.2	3.6	4.0
10km/h	3570	3970	4370	4780	5180	5580	5980	6380	6670	6840	7190	7530	7880
25 km/h	3020	3390	3760	4120	4490	4860	5230	5590	5850	6010	6310	6610	6910
40km/h	2640	2950	3260	3570	3880	4190	4510	4820	5040	5170	5430	5690	5950
50 km/h	2340	2620	2890	3170	3450	3730	4010	4290	4480	4600	4830	5060	5290
65 km/h	1950	2180	2410	2640	2860	3090	3320	3540	3710	3800	3990	4180	4380

* check load capacity of rim



FLOTXTRA



DE MOLEN
BANDEN

RUSTVENSEWEG 2 - 5375KW - REEK
TEL: 0486-479727
WWW.DEMOLENBANDEN.NL