



- **Full steel construction** extremely robust to perforation
- Optimum protection of grass sward and crops by rounded shoulders
- Excellent lateral grip by special block design with multi oriented faces
- Limited stone and mud retention due to optimum tread geometry
- Excellent directional stability due nearly continuous central rib & tread stiffness

Technical data

Load index speed symbol	165D	Type	TL
Diameter (mm)	1333	Width (mm)	611
Tread depth (mm)	20	Rim	20.00 x 26.5
Static load radius (mm)	600	Rolling circumference (mm)	4040

Load capacity per tire (kg) according to ETRTO* | Inflation pressure

Bar	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
10km/h	3895	4730	5470	6280	6970	7790	8530	9270
25 km/h	3420	4150	4825	5510	6120	6840	7490	8140
40km/h	2985	3625	4190	4810	5325	5965	6535	7100
50 km/h	2620	3160	3680	4220	4710	5240	5740	6235
65 km/h	2165	2630	3040	3480	3865	4330	4740	5150

* check load capacity of rim



FLOTXTRA



DE MOLEN
BANDEN

RUSTVENSEWEG 2 - 5375KW - REEK
TEL: 0486 - 479727
WWW.DEMOLENBANDEN.NL