



- **Full steel construction** extremely robust to perforation
- Optimum protection of grass sward and crops by rounded shoulders
- Excellent lateral grip by special block design with multi oriented faces
- Limited stone and mud retention due to optimum tread geometry
- Excellent directional stability due nearly continuous central rib & tread stiffness

#### Technical data

Load index   speed symbol	169D	Type	TL
Diameter (mm)	1389	Width (mm)	645
Tread depth (mm)	20	Rim	20.00 x 26.5
Static load radius (mm)	625	Rolling circumference (mm)	4210

#### Load capacity per tire (kg) according to ETRTO\* | Inflation pressure

Bar	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
10km/h	4385	5325	6160	7100	8040	8670	9605	10440
25 km/h	3850	4675	5410	6235	7060	7610	8435	9165
40km/h	3360	4080	4720	5440	6160	6640	7360	8000
50 km/h	2950	3585	4145	4775	5410	5830	6460	7020
65 km/h	2440	2960	3425	3945	4470	4815	5340	5800

\* check load capacity of rim



**FLOTXTRA**



**DE MOLEN**  
BANDEN

RUSTVENSEWEG 2 - 5375KW - REEK  
TEL: 0486-479727  
WWW.DEMOLENBANDEN.NL