



- **Full steel construction** extremely robust to perforation
- Optimum protection of grass sward and crops by rounded shoulders
- Excellent lateral grip by special block design with multi oriented faces
- Limited stone and mud retention due to optimum tread geometry
- Excellent directional stability due nearly continuous central rib & tread stiffness

#### Technical data

Load index   speed symbol	176D	Type	TL
Diameter (mm)	1621	Width (mm)	645
Tread depth (mm)	23	Rim	20.00 x 30.5
Static load radius (mm)	729	Rolling circumference (mm)	4910

#### Load capacity per tire (kg) according to ETRTO\* | Inflation pressure

Bar	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
10 km/h	5370	6520	7545	8695	9845	10610	11760	12780
25 km/h	4715	5725	6620	7630	8640	9315	10325	11220
40 km/h	4060	4930	5700	6570	7440	8020	8890	9660
50 km/h	3610	4385	5075	5845	6620	7135	7910	8595
65 km/h	2985	3625	4190	4830	5470	5895	6535	7100

\* check load capacity rim



**FLOTXTRA**



**DE MOLEN**  
BANDEN

RUSTVENSEWEG 2 - 5375KW - REEK  
TEL: 0486 - 479727  
WWW.DEMOLENBANDEN.NL