



- **Full steel construction** extremely robust to perforation
- Optimum protection of grass sward and crops by rounded shoulders
- Excellent lateral grip by special block design with multi oriented faces
- Limited stone and mud retention due to optimum tread geometry
- Excellent directional stability due nearly continuous central rib & tread stiffness

Technical data

Load index speed symbol	161D	Type	TL
Diameter (mm)	1140	Width (mm)	727
Tread depth (mm)	18	Rim	24.00 x 22.5
Static load radius (mm)	513	Rolling circumference (mm)	3455

Load capacity per tire (kg) according to ETRTO* | Inflation pressure

Bar	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
10km/h	3500	4160	4915	5600	6265	6995	7660	8325
25 km/h	3075	3660	4300	4910	5500	6120	6730	7310
40km/h	2650	3150	3720	4240	4750	5280	5800	6300
50 km/h	2355	2830	3305	3780	4210	4690	5155	5600
65 km/h	1945	2320	2730	3100	3500	3870	4255	4625

* check load capacity rim



FLOTXTRA



DE MOLEN
BANDEN

RUSTVENSEWEG 2 - 5375KW - REEK
TEL: 0486-479727
WWW.DEMOLENBANDEN.NL