



- **Full steel construction** extremely robust to perforation
- Optimum protection of grass sward and crops by rounded shoulders
- Excellent lateral grip by special block design with multi oriented faces
- Limited stone and mud retention due to optimum tread geometry
- Excellent directional stability due nearly continuous central rib & tread stiffness

Technical data

Load index speed symbol	170D	Type	TL
Diameter (mm)	1383	Width (mm)	727
Tread depth (mm)	20	Rim	24.00 x 26.5
Static load radius (mm)	622	Rolling circumference (mm)	4190

Load capacity per tire (kg) according to ETRTO* | Inflation pressure

Bar	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
10km/h	4540	5510	6375	7225	8120	9075	9940	10800
25 km/h	3985	4810	5595	6410	7150	7965	8725	9480
40km/h	3465	4190	4870	5590	6210	6930	7590	8250
50 km/h	3050	3700	4285	4930	5475	6100	6680	7260
65 km/h	2520	3060	3550	4050	4530	5040	5520	6000

* check load capacity of rim



FLOTXTRA



DE MOLEN
BANDEN

RUSTVENSEWEG 2 - 5375KW - REEK
TEL: 0486-479727
WWW.DEMOLENBANDEN.NL