



- **Full steel construction** extremely robust to perforation
- Optimum protection of grass sward and crops by rounded shoulders
- Excellent lateral grip by special block design with multi oriented faces
- Limited stone and mud retention due to optimum tread geometry
- Excellent directional stability due nearly continuous central rib & tread stiffness

Technical data

Load index speed symbol	181D	Type	TL
Diameter (mm)	1675	Width (mm)	754
Tread depth (mm)	23	Rim	24.00 x 30.5
Static load radius (mm)	754	Rolling circumference (mm)	5075

Load capacity per tire (kg) according to ETRTO* | Inflation pressure

Bar	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
10 km/h	6240	7575	8765	10100	11435	12330	13665	14850
25 km/h	5475	6650	7695	865	10040	10820	11995	13035
40 km/h	4715	5725	6620	7630	8640	9315	10325	11220
50 km/h	4195	5095	5895	6790	7690	8290	9190	9985
65 km/h	3465	4210	4870	5610	6355	6850	7590	8250

* check load capacity rim



FLOTXTRA



DE MOLEN
BANDEN

RUSTVENSEWEG 2 - 5375KW - REEK
TEL: 0486-479727
WWW.DEMOLENBANDEN.NL