



- **Full steel construction** extremely robust to perforation
- Optimum protection of grass sward and crops by rounded shoulders
- Excellent lateral grip by special block design with multi oriented faces
- Limited stone and mud retention due to optimum tread geometry
- Excellent directional stability due nearly continuous central rib & tread stiffness

Technical data

Load index speed symbol	174D	Type	TL
Diameter (mm)	1393	Width (mm)	828
Tread depth (mm)	20	Rim	28.00 x 26.5
Static load radius (mm)	627	Rolling circumference (mm)	4220

Load capacity per tire (kg) according to ETRTO* | Inflation pressure

Bar	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
10 km/h	5070	6140	7120	8160	9085	10135	11100	12060
25 km/h	4450	5400	6250	7160	7985	8900	9745	10590
40 km/h	3780	4570	5310	6080	6785	7560	8280	9000
50 km/h	3410	4120	4785	5500	6100	6815	7465	8110
65 km/h	2815	3400	3955	4540	5050	5630	6165	6700

* check load capacity of rim



FLOTXTRA



DE MOLEN
BANDEN

RUSTVENSEWEG 2 - 5375KW - REEK
TEL: 0486-479727
WWW.DEMOLENBANDEN.NL