

MAXAM AGRIXTRA 65

MS951R - R1W RADIAL DRIVE TIRE VF/SERIES

Extra wide profile 65-series tire for high flotation and traction. Premium 45° lug profile provides excellent traction and minimizes vibration while roading. Low pressure and wide footprint lowers soil compaction.

- ▶ Radial tire construction
- ▶ Self-cleaning tread design
- ▶ Wide tread for maximized performance in the field
- ▶ Low pressure for minimal soil disturbance
- ▶ Premium rubber compounds reduce ozone cracking and weathering



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



Item Number	Size	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. Vol. gal l	# of Lugs	Gross Flat Plate sq in sq cm
						in	mm	in	mm	in	mm	in	mm						
951116	440/65R24	128D	TL	W14L	W13, W15L	17.4	442	46.5	1182	20	508	139.2	3534	37 575	53 42	172 78	51.5 195	18 x 2	190 1225
951201	480/65R24	133D	TL	W15L	W14L, DW14L, DW15L	18.9	479	48.6	1234	21.6	548	145.3	3690	38 600	54 43	198 90	52.3 198	18 x 2	217 1403
951217	540/65R24	140D	TL	W16L	DW16L, W18L, DW18L	20.9	530	51.7	1312	22	559	154.5	3923	39 625	58 46	247 112	80 303	18 x 2	264 1702
951119	420/65R28	128D	TL	W13	W11, W12	16.5	418	49.5	1257	21.2	538	148	3758	39 600	52 41	170 77	57 216	18 x 2	190 1225
951200	440/65R28	131D	TL	W14L	W13, DW14L, W15L, DW15L	17.4	442	50.5	1283	22.8	579	151.1	3836	39 625	53 42	190 86	47.3 179	18 x 2	206 1328
951202	480/65R28	136D	TL	W15L	W14L, DW14L, DW15L	18.9	479	52.6	1335	23.6	599	157.2	3992	40 650	54 43	216 98	58.6 222	18 x 2	236 1525
951203	540/65R28	142D	TL	W16L	DW16L, W18L, DW18L	20.9	530	55.6	1413	24.8	629	166.4	4225	41 675	58 46	271 123	77.1 292	19 x 2	280 1804

TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS

Continued



Item Number	Size	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. Vol. gal l	# of Lugs	Gross Flat Plate sq in sq cm
						in	mm	in	mm	in	mm	in	mm						
V951132	540/65R30	150D	TL	W16L	DW16L, W18L, DW18L	20.9	530	57.6	1464	25.8	655	172.4	4377	41 700	63 50	318 144	79.7 302	19 x 2	265 1711
951122	540/65R34	145D	TL	W16L	DW16L, W18L, DW18L	20.9	530	61.7	1566	25.9	658	184.4	4682	43 705	64 51	329 149	121.2 459	20 x 2	306 1974
V951149	600/65R34	151D	TL	DW20B	W18L	24.1	611	64.7	1644	29	736	193.6	4916	43 775	66 52	375 170	118.3 448	20 x 2	364.1 2349
951215	540/65R38	147D	TL	W16L	DW16L, W18L, DW18L	20.9	530	65.6	1667	27.5	698	196.3	4984	44 800	64 51	364 165	140.2 531	20 x 2	325 2094
951205	600/65R38	153D	TL	DW20B	W18L, DW18L, DW20A	24.1	611	68.7	1745	31	787	205.5	5218	45 825	66 52	401 182	129.4 490	20 x 2	385 2485
V951146	650/65R38	166D	TL	DW20B	DW20A	25.4	645	71.3	1810	32	812	213.1	5412	46 875	71 56	536 243	151.3 573	20 x 2	419 2706
951133	650/65R42	165D	TL	DW20B	DW20A	25.4	645	75.3	1912	34	863	225.1	5717	47 925	73 58	531 241	163.4 619	21 x 2	449 2894

TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS VF/SERIES

Item Number	Size	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. vol. gal l	# of Lugs	Gross Flat Plate sq in sq cm
						in	mm	in	mm	in	mm	in	mm						
V951533	VF650/65R42	170D	TL	DW21B	DW23B	25.6	650	75.3	1913	33.2	843	229.1	5820	47 925	74 59	559 254	160.6 608	21 x 2	595 3841

MAXAM AGRIXTRA 65

MS951R - R1W RADIAL DRIVE TIRE

VF/SERIES

Extra wide profile 65-series tire for high flotation and traction. Premium 45° lug profile provides excellent traction and minimizes vibration while roading. Low pressure and wide footprint lowers soil compaction.

- ▶ Radial tire construction
- ▶ Self-cleaning tread design
- ▶ Wide tread for maximized performance in the field
- ▶ Low pressure for minimal soil disturbance
- ▶ Premium rubber compounds reduce ozone cracking and weathering



AGRIXTRA 65 LOAD AND INFLATION

Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)														
			9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	27 psi	29 psi	32 psi	35 psi	38 psi	41 psi			
			0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.9 bar	2 bar	2.2 bar	2.4 bar	2.6 bar	2.8 bar			
440/65R24	128D	5/10 LT	3210/1455	3625/1645	4055/1840	4485/2035	4905/2225	5335/2420	5955/2700								
		40/65			3020/1370	3330/1510	3650/1655	3970/1800									
480/65R24	133D	5/10 LT	3660/1660	4155/1885	4640/2105	5125/2325	5625/2550	6110/2770	6815/3090								
		40/65			3450/1565	3815/1730	4180/1895	4540/2060									
540/65R24	140D	5/10 LT	4455/2020	5040/2285	5635/2555	6230/2825	6825/3095	7420/3365	8270/3750								
		40/65			4190/1900	4630/2100	5070/2300	5515/2500									
420/65R28	128D	5/10 LT	3210/1455	3625/1645	4055/1840	4485/2035	4905/2225	5335/2420	5955/2700								
		40/65			3020/1370	3330/1510	3650/1655	3970/1800									
440/65R28	131D	5/10 LT	3475/1575	3935/1785	4400/1995	4860/2205	5325/2415	5790/2625	6450/2925								
		40/65			3265/1480	3615/1640	3960/1795	4300/1950									
480/65R28	136D	5/10 LT	3990/1810	4520/2050	5050/2290	5580/2530	6110/2770	6650/3015	7410/3360								
		40/65			3750/1700	4145/1880	4540/2060	4940/2240									
540/65R28	142D	5/10 LT	4720/2140	5345/2425	5975/2710	6605/2995	7230/3280	7860/3565	8765/3975								
		40/65			4445/2015	4905/2225	5380/2440	5845/2650									



AGRIXTRA 65 LOAD AND INFLATION

Continued

Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)														
			9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	27 psi	29 psi	32 psi	35 psi	38 psi	41 psi			
			0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.9 bar	2 bar	2.2 bar	2.4 bar	2.6 bar	2.8 bar			
540/65R30	150D	5/10 LT	4145/1880	4695/2130	5250/2380	5800/2630	6360/2885	6915/3135	7310/3315	7705/3495	8105/3675	8500/3855					
		40/65			4565/2070	5050/2290	5525/2505	6010/2725	6350/2880	6705/3040	7045/3195	7385/3350					
540/65R34	145D	5/10 LT	5160/2340	5845/2650	6540/2965	7220/3275	7915/3590	8600/3900	9590/4350								
		40/65			4860/2205	5370/2435	5885/2670	6395/2900									
600/65R34	151D	5/10 LT	6140/2785	6955/3155	7775/3525	8600/3900	9415/4270	10230/4640	11410/5175								
		40/65			5775/2620	6395/2900	7000/3175	7605/3450									
540/65R38	147D	5/10 LT	5470/2480	6195/2810	6935/3145	7660/3475	8390/3805	9120/4135	10175/4615								
		40/65			5150/2335	5700/2585	6240/2830	6780/3075									
600/65R38	153D	5/10 LT	6495/2945	7365/3340	8225/3730	9095/4125	9955/4515	10825/4910	12070/5475								
		40/65			6120/2775	6760/3065	7410/3360	8050/3650									
650/65R38	166D	5/10 LT	7345/3330	8325/3775	9295/4215	10275/4660	11255/5105	12240/5550	12790/5800	13350/6055	13905/6305	14455/6555	15150/6870	15830/7180			
		40/65			6915/3135	7640/3465	8370/3795	9095/4125	9515/4315	9925/4500	10340/4690	10750/4875	11255/5105	11685/5300			
650/65R42	165D	5/10 LT	7565/3430	8565/3885	9580/4345	10585/4800	11600/5260	12600/5715	13635/6185	14075/6385	14815/6720	15255/6920	16150/7325	16590/7525			
		40/65			7120/3230	7870/3570	8620/3910	9370/4250	10140/4600	10500/4750	11000/5000	11400/5150	12000/5450	12300/5600			

AGRIXTRA 65 LOAD AND INFLATION VF/SERIES

Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)														
			9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	27 psi	29 psi	32 psi	35 psi	38 psi	41 psi			
			0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.9 bar	2 bar	2.2 bar	2.4 bar	2.6 bar	2.8 bar			
VF650/65R42	170D	5/10	8140/3685	9680/4400	10890/4950	12100/5500	13530/6160	14520/6600									
		40/65	7400/3350	8800/4000	9900/4500	11000/5000	12300/5600	13200/6000									

*LT = Low Torque

MAXAM AGRIXTRA 70

MS951R - R1W RADIAL DRIVE TIRE

Wide profile 70-series tire for extra flotation and traction. Premium 45° lug profile provides excellent traction and minimizes vibration while roading. Low pressure and wide footprint lowers soil compaction.

- ▶ Radial tire construction
- ▶ Self-cleaning tread design
- ▶ Wide tread for maximized performance in the field
- ▶ Low pressure for minimal soil disturbance
- ▶ Premium rubber compounds reduce ozone cracking and weathering



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



Item Number	Size	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. vol. gal l	# of lugs	Gross Flat Plate sq in sq cm
						in	mm	in	mm	in	mm	in	mm						
951518	260/70R16	109D	TL	W8	W7	9.9	252	30.8	781	13.6	345	90.6	2300	29 350	39 31	46 21	10.6 40	17 x 2	92 591
951519	280/70R16	112D	TL	W9	W7, W8	10.7	272	31.6	802	14.1	357	93.7	2380	30 375	40 32	55 25	12.7 48	17 x 2	93 600
951523	280/70R18	114D	TL	W9	W8, W10	10.9	278	33.6	854	15.1	383	100.5	2553	32 400	40 32	60 27	12.2 46	17 x 2	100 643
951520	260/70R20	113D	TL	W8	W7	9.8	248	34.7	881	15.5	394	103.4	2627	32 425	39 31	55 25	11.6 44	17 x 2	98 632
951521	280/70R20	116D	TL	W9	W7, W8	10.7	271	35.9	911	16	407	106.8	2713	32 425	40 32	63 29	14.3 54	17 x 2	108 695
951522	300/70R20	120D	TL	W9	W8, W10	11.5	292	37.7	958	16.7	424	111.3	2827	33 450	42 33	69 31	17.2 65	17 x 2	124 797
951100	360/70R24	122A8/B	TL	W11	W10, W12	13.9	352	45.4	1152	20.3	516	135.6	3444	37 550	50 40	139 63	31.2 118	17 x 2	158 1021
951101	380/70R24	125A8/B	TL	W12	W11, W13	14.8	376	46.9	1190	20.9	531	140.1	3558	37 575	52 41	157 71	37 140	17 x 2	174 1123
951103	420/70R24	130A8/B	TL	W13	W12, W14L	16.7	424	49.1	1248	21.8	554	147	3732	38 600	53 42	181 82	47.3 179	18 x 2	201 1294
V951129	480/70R24	138D	TL	W15L	W14L, DW14L, DW15L, W16L, DW16L	18.9	479	51.8	1316	22.8	580	154.9	3935	39 625	55 44	227 103	63.1 239	18 x 2	249 1607
951209	360/70R28	125A8	TL	W11	W10, W12	14.3	364	49.3	1251	22.3	566	147.3	3740	32 600	50 40	148 67	34.8 132	18 x 2	174 1123
951102	380/70R28	127A8/B	TL	W12	W11, W13	15	380	50.9	1293	23	583	152.2	3866	39 575	52 41	170 77	41.7 158	18 x 2	185 1191

TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



Continued

Item Number	Size	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. vol. gal l	# of lugs	Gross Flat Plate sq in sq cm
						in	mm	in	mm	in	mm	in	mm						
951105	420/70R28	133A8/B	TL	W13	W12, W14L	16.6	422	53.1	1349	23.8	604	158.8	4034	40 650	53 42	198 90	52.8 200	18 x 2	217 1403
951104	480/70R28	140A8/B	TL	W15L	W14L, DW14L, DW15L, W16L, DW16L	19.1	484	56	1421	24.9	632	167.3	4249	41 675	55 44	249 113	71 269	19 x 2	264 1702
951112	520/70R30	145A8	TL	W16L	W15L, W18L	20.3	515	60.5	1536	26.9	683	180.9	4593	42 725	63 50	304 138	90 341	20 x 2	306 1974
V951130	480/70R30	152D	TL	W15L	W14L, DW14L, DW15L, W16L, DW16L	19	483	58.2	1478	26	660	174	4419	42 700	60 48	309 140	74.4 282	19 x 2	241 1554
V951131	480/70R34	155A8/B	TL	W15L	W14L, DW14L, DW15L, W16L, DW16L	18.9	479	62.2	1580	28	711	186	4724	43 750	60 48	333 151	82.1 311	19 x 2	263 1696
951121	520/70R34	148A8	TL	W16L	W15L, W18L	20.1	511	64.6	1640	28.9	735	193.1	4904	44 775	63 50	332 150	99.3 376	20 x 2	332 2145
951214	480/70R38	145A8/B	TL	W15L	W14L, W16L	19.4	493	66.2	1681	30	762	197.9	5026	44 800	87 45	319 145	89.5 339	20 x 2	306 1974
951108	520/70R38	150A8/B	TL	W16L	W15L, DW15L, DW16L, W18L, DW18L	20.3	516	68.9	1749	31	788	205.9	5230	45 825	63 50	366 166	109.6 415	20 x 2	354 2281
951109	580/70R38	155A8/B	TL	W18L	DW18L	22.8	578	71.9	1827	32.2	819	215.1	5463	46 875	71 56	444 202	138.9 526	21 x 2	409 2638
951124	620/70R42	166D	TL	DW20B		24.6	625	76.2	1935	34.3	872	227.8	5786	47 925	73 58	512 232	163.7 620	22 x 2	419 2706
V951526	620/70R46	162D	TL	DW20B	DW18L, W18L	24.6	625	80.2	2036	36	914	228.8	5812	48 975	73 58	575 261	173 655	22 x 2	547 3531

MAXAM AGRIXTRA 70

MS951R - R1W RADIAL DRIVE TIRE

AGRIXTRA 70 LOAD AND INFLATION

Metric Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)											
			9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	26 psi	27 psi	29 psi	32 psi	35 psi	41 psi
			0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	1.9 bar	2 bar	2.2 bar	2.4 bar	2.8 bar
260/70R16	109D	5/10 LT	1410/640	1610/730	1810/820	2040/920	2220/1000	2490/1130	2740/1240		2980/1350	3200/1450	3420/1550	
		40/65		1070/490	1200/540	1360/610	1480/670	1650/750	1810/820		1980/900	2120/960	2270/1030	
280/70R16	112D	5/10 LT	1570/710	1810/820	2050/930	2290/1040	2500/1130	2820/1280	3060/1390		3310/1500	3500/1590	3700/1680	
		40/65		1200/540	1360/620	1520/690	1660/750	1870/850	2090/950		2320/1040	2390/1080	2470/1120	
280/70R18	114D	5/10 LT	1440/655	1695/770	1940/880	2190/995	2435/1105	2645/1200	2865/1300		3105/1410	3330/1510	3525/1600	
		40/65		1300/590	1440/655	1630/740	1815/825	1970/895	2125/965		2310/1050	2425/1115	2600/1180	
260/70R20	113D	5/10 LT	1600/730	1830/830	2060/930	2300/1040	2510/1140	2830/1280	3070/1390		3320/1500	3560/1610	3800/1730	
		40/65		1210/550	1370/620	1540/700	1680/760	1880/850	2140/9970		2410/1090	2480/1120	2540/1150	
280/70R20	116D	5/10 LT	1690/770	1980/900	2270/1030	2560/1160	2790/1270	3140/1430	3420/1550		3700/1680	3910/1770	4130/1880	
		40/65		1320/600	1520/690	1710/780	1860/840	2090/950	2280/1030		2470/1120	2610/1180	2760/1250	
300/70R20	120D	5/10 LT	1970/890	2230/1010	2490/1130	2750/1250	3050/1380	3510/1590	3830/1740		4150/1880	4390/1990	4630/2100	
		40/65		1480/670	1650/750	1820/830	2030/920	2340/1060	2550/1160		2760/1250	2920/1320	3080/1400	
360/70R24	122A8/B	5/10 LT	2985/1355	3285/1490	3585/1625	3880/1760	4180/1895	4485/2035		4960/2250				
		25/40 & 30/50		2425/1100	2645/1200	2865/1300	3085/1400	3305/1500						
380/70R24	125A8/B	5/10 LT	3285/1490	3615/1640	3945/1790	4275/1940	4595/2085	4925/2235		5455/2475				
		25/40 & 30/50		2670/1210	2910/1320	3155/1430	3395/1540	3640/1650						
420/70R24	130A8/B	5/10 LT	3780/1715	4165/1890	4540/2060	4915/2230	5300/2405	5675/2575		6285/2850				
		25/40 & 30/50		3075/1395	3350/1520	3625/1645	3915/1775	4190/1900						
480/70R24	138D	5/10 LT	4200/1905	4765/2160	5315/2410	5875/2665	6440/2920	7000/3175		7805/3540				
		40/65			3960/1795	4365/1980	4785/2170	5205/2360						
360/70R28	125A8/B	5/10 LT	3285/1490	3615/1640	3945/1790	4275/1940	4595/2085	4925/2235		5455/2475				
		25/40 & 30/50		2670/1210	2910/1320	3155/1430	3395/1540	3640/1650						
380/70R28	127A8/B	5/10 LT	3485/1580	3835/1740	4180/1895	4530/2055	4885/2215	5225/2370		5785/2625				
		25/40 & 30/50		2835/1285	3085/1400	3340/1515	3605/1635	3860/1750						
420/70R28	133A8/B	5/10 LT	4100/1860	4510/2045	4925/2235	5335/2420	5745/2605	6150/2790		6810/3090				
		25/40 & 30/50		3330/1510	3640/1650	3935/1785	4245/1925	4540/2060						
480/70R28	140A8/B	5/10 LT	4980/2260	5480/2485	5975/2710	6470/2935	6965/3160	7475/3390		8265/3750				
		25/40 & 30/50		4045/1835	4410/2000	4775/2165	5150/2335	5510/2500						
520/70R30	145A8/B	5/10 LT	5775/2620	6350/2880	6935/3145	7505/3405	8090/3670	8665/3930		9590/4350				
		25/40 & 30/50		4685/2125	5115/2320	5545/2515	5965/2705	6395/2900						
520/70R34	148A8/B	5/10 LT	6270/2845	6900/3130	7530/3415	8155/3700	8785/3985	9415/4270		10415/4725				
		25/40 & 30/50		5095/2310	5555/2520	6020/2730	6480/2940	6945/3150						
480/70R38	145A8/B	5/10 LT	5775/2620	6350/2880	6935/3145	7505/3405	8090/3670	8665/3930		9590/4350				
		25/40 & 30/50		4685/2125	5115/2320	5545/2515	5965/2705	6395/2900						

*LT = Low Torque

AGRIXTRA 70 LOAD AND INFLATION

Continued

Metric Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)											
			9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	26 psi	27 psi	29 psi	32 psi	35 psi	41 psi
			0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	1.9 bar	2 bar	2.2 bar	2.4 bar	2.8 bar
520/70R38	150A8/B	5/10 LT	6670/3025	7340/3330	8005/3630	8675/3935	9335/4235	10010/4540		11080/5025				
		25/40 & 30/50		5410/2455	5910/2680	6405/2905	6890/3125	7385/3350						
580/70R38	155A8/B	5/10 LT	7715/3500	8490/3850	9260/4200	10030/4550	10805/4900	11575/5250		12820/5815				
		25/40 & 30/50		6260/2840	6835/3100	7410/3360	7970/3615	8545/3875						
620/70R42	166D	5/10 LT	8005/3630	9075/4115	10145/4600	11210/5085	12280/5570	13350/6055	13935/6320		14530/6590	15125/6860	15720/7130	17530/7950
		40/65			7540/3420	8335/3780	9130/4140	9925/4500	10365/4700		10805/4900	11245/5100	11685/5300	
620/70R46	162D	5/10 LT	7640/3465	8875/4035	10220/4640	11500/5210	12575/5715	14125/6390						
		40/65		5680/2575	6600/3000	7600/3450	8550/3875	9350/4250	10500/4750					
Metric Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)											
			12 psi	15 psi	18 psi	20 psi	23 psi	26 psi	29 psi					
			0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	2 bar					
480/70R30	152D	5/10 LT	5195/2355	5800/2630	6415/2910	7025/3185	7640/3465	8005/3630	8380/3800					
		40/65		4310/1955	4775/2165	5225/2370	5680/2575	5955/2700	6230/2825					
480/70R34	155A8/B	5/10 LT	5975/2710	6515/2955	7055/3200	7595/3445	8135/3690	8535/3870	8930/4050					
		25/40 & 30/50		4410/2000	4805/2180	5205/2360	5610/2545	6010/2725	6295/2855	6595/2990				
Metric Size	LI / SS	Service Speed (mph/kph)	(continued) TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)											
			32 psi	35 psi	38 psi	41 psi	44 psi	46 psi						
			2.2 bar	2.4 bar	2.6 bar	2.8 bar	3 bar	3.2 bar						
480/70R30	152D	5/10 LT	8755/3970	9120/4135	9470/4295	9825/4455	10175/4615	10530/4775						
		40/65		6505/2950	6780/3075	7045/3195	7310/3315	7565/3430	7830/3550					
480/70R34	155A8/B	5/10 LT	9315/4225	9715/4405	10175/4615	10640/4825	11115/5040	11575/5250						
		25/40 & 30/50		6880/3120	7165/3250	7510/3405	7860/3565	8205/3720	8545/3875					

*LT = Low Torque

MAXAM AGRIXTRA 85

MS951R - R1W RADIAL DRIVE TIRE

VF/SERIES

Premium 45° lug profile provides excellent traction and minimizes vibration while roading. Low pressure and wide footprint lowers soil compaction.

- ▶ Radial tire construction
- ▶ Self-cleaning tread design
- ▶ Wide tread for maximized performance in the field
- ▶ Low pressure for minimal soil disturbance
- ▶ Premium rubber compounds reduce ozone cracking and weathering



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



Item Number	Metric Size	Alt Size	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. vol. gal l	# of lugs	Gross Flat Plate sq in sq cm
							in	mm	in	mm	in	mm	in	mm						
921215	250/85R24	9.5R24	109A8/B	TL	W8	W7, W9	9.9	251	40.8	1035	18.5	471	121.9	3095	35 500	48 38	86 39	14.8 56	19 x 2	109 701
V951000	280/85R24	11.2R24	115A8/B	TL	W10	W9	11.5	292	42.8	1086	19.3	491	127.9	3247	36 525	50 40	99 45	20.6 78	19 x 2	128 827
V951002	320/85R24	12.4R24	122A8/B	TL	W11	W10	13	329	45.4	1154	20.4	517	135.9	3450	37 550	52 41	121 55	28.8 109	19 x 2	158 1021
V951004	340/85R24	13.6R24	125A8/B	TL	W12	W11	13.9	353	46.8	1188	20.9	530	139.9	3552	37 575	53 42	135 61	33.8 128	19 x 2	174 1123
V951008	380/85R24	14.9R24	131A8/B	TL	W13	W12	15.4	390	49.5	1256	21.9	557	147.9	3755	39 600	54 43	168 76	44.6 169	19 x 2	206 1328
V951011	420/85R24	16.9R24	137A8/B	TL	W15L	W14L, DW14L, DW15L	17.2	438	52.1	1324	23	583	155.9	3959	40 625	58 46	203 92	58.1 220	20 x 2	243 1566
951001	280/85R28	11.2R28	118A8/B	TL	W10	W9	11.5	292	46.7	1187	21.3	541	139.7	3549	37 575	50 40	114 52	23.2 88	19 x 2	139 899
951003	320/85R28	12.4R28	124A8/B	TL	W11	W10	13	329	49.4	1255	22.4	568	147.7	3752	39 600	52 41	134 61	32.2 122	19 x 2	169 1089
V951005	340/85R28	13.6R28	127A8/B	TL	W12	W11	13.9	353	50.8	1289	22.9	581	151.8	3854	39 625	53 42	150 68	38 144	20 x 2	185 1191

TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS

Continued



Item Number	Metric Size	Alt Size	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. vol. gal l	# of lugs	Gross Flat Plate sq in sq cm
							in	mm	in	mm	in	mm	in	mm						
V951009	380/85R28	14.9R28	133A8/B	TL	W13	W12	15.4	390	53.4	1357	23.9	607	159.8	4057	40 650	54 43	187 85	49.9 189	20 x 2	217 1403
V951012	420/85R28	16.9R28	139A8/B	TL	W15L	W14L, DW14L, DW15L	17.2	438	56.1	1425	25	634	167.8	4261	41 675	58 46	221 100	64.7 245	20 x 2	256 1654
V951010	380/85R30	14.9R30	135A8/B	TL	W13	W12	15.4	390	55.4	1408	24.9	633	165.8	4210	41 675	54 43	201 91	52.5 199	20 x 2	230 1484
V951013	420/85R30	16.9R30	140A8/B	TL	W15L	W14L, DW14L, DW15L	17.2	438	58.1	1476	25.9	659	173.8	4413	42 700	63 50	238 108	67.1 254	20 x 2	264 1702
V951020	460/85R30	18.4R30	145A8/B	TL	W16L	W14L, W15L	18.7	475	60.8	1544	27	686	181.8	4617	42 725	64 51	276 125	83.7 317	20 x 2	306 1974
V951220	320/85R32	12.4R32	126A8/B	TL	W11	W9, W10	13	329	53.4	1357	23.4	619	159.7	4057	40 650	52 41	154 70	35.9 136	20 x 2	179 1157
V951221	380/85R34	14.9R34	146A8/B	TL	W12	W13	15	380	59.5	1510	23.4	684	159.7	4515	42 750	54 43	238 108	56.2 213	20 x 2	237 1532
V951014	420/85R34	16.9R34	142A8/B	TL	W15L	W14L, DW14L, DW15L	17.2	438	62.1	1578	28	710	185.8	4718	43 750	63 50	260 118	73.7 279	20 x 2	280 1804

MAXAM AGRIXTRA 85

MS951R - R1W RADIAL DRIVE TIRE

VF/SERIES

Premium 45° lug profile provides excellent traction and minimizes vibration while roading. Low pressure and wide footprint lowers soil compaction.

- ▶ Radial tire construction
- ▶ Self-cleaning tread design
- ▶ Wide tread for maximized performance in the field
- ▶ Low pressure for minimal soil disturbance
- ▶ Premium rubber compounds reduce ozone cracking and weathering



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS

Continued



Item Number	Metric Size	Alt Size	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. vol. gal l	# of lugs	Gross Flat Plate sq in sq cm
							in	mm	in	mm	in	mm	in	mm						
V951016	460/85R34	18.4R34	147A8/B	TL	W16L	W15L, DW15L, DW16L	18.7	475	64.8	1646	29	737	193.8	4922	44 775	64 51	298 135	91.9 348	20 x 2	325 2094
951210	320/85R36	12.4R36	128A8/B	TL	W11	W10	13	329	57.4	1458	26.3	669	171.6	4359	41 700	52 41	163 74	39.6 150	20 x 2	190 1225
951006	340/85R36	13.6R36	132A8/B	TL	W12	W11	13.9	353	58.8	1492	26.9	682	175.7	4461	42 725	58 46	192 87	45.4 172	21 x 2	211 1362
951007	340/85R38	13.6R38	133A8/B	TL	W12	W11	13.9	353	60.8	1543	27.9	708	181.7	4614	42 750	58 46	198 90	47.5 180	21 x 2	217 1403
V951222	380/80R38	14.9R38	142A8/B	TL	W12	W11, W13	15	380	61.9	1573	23.4	720	159.7	4703	43 750	57 45	234 106	57.3 217	20 x 2	210 1353
V951015	420/85R38	16.9R38	144A8/B	TL	W15L	W14L, DW14L, DW15L	17.2	438	66.1	1679	30	761	197.7	5020	44 800	63 50	280 127	80.3 304	21 x 2	295 1906
V951017	460/85R38	18.4R38	149A8/B	TL	W16L	W15L, DW15L, DW16L	18.7	475	68.8	1747	31	788	205.7	5224	45 825	64 51	324 147	99.8 378	21 x 2	343 2213
V951018	520/85R38	20.8R38	155A8/B	TL	DW18L	W16L, DW16L, W18L	21.1	536	72.8	1849	32.6	827	217.7	5529	46 875	67 53	404 183	134.9 511	21 x 2	409 2638
951216	460/85R42	18.4R42	156A8/B	TL	W16L	W14L, W15L	18.7	475	72.7	1846	33	837	217.4	5520	46 875	64 51	399 181	107.4 407	21 x 2	422 2723
V951110	480/80R42	18.4R42	151A8/B	TL	W16A	W16L, DW16L	19.3	489	72.8	1849	33	838	217.7	5529	46 875	64 51	373 169	111.4 422	21 x 2	364 2349

TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS

Continued



Item Number	Metric Size	Alt Size	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. vol. gal l	# of lugs	Gross Flat Plate sq in sq cm
							in	mm	in	mm	in	mm	in	mm						
V951131	520/85R42	20.8R42	167D	TL	DW18L	W16L, DW16L, W18L			76.8	1951	34.6	878	229.7	5833	47 925	66.8 53	485 220	145.7 552	22 x 2	370 2305
V951111	480/80R46	18.4R46	158A8/B	TL	W16A	W16L, DW16L, DD16L	19.3	489	76.2	1936	34.8	884	228	5789	47 925	64 51	417 189	117.2 444	21 x 2	336 2170
V951113	520/85R46	20.8R46	158A8/B	TL	W16A	W18L, DW18L, DD18L	20.3	516	80.8	2052	36.6	929	241.6	6135	48 975	69 55	496 225	149.2 565	22 x 2	449 2894
V951224	480/80R50	18.4R50	176A8/B	TL	DW16L	W16L, DW15L, W15L	19.8	503	80.4	2043	37.5	952	240	6094	48 975	66 52	549 249	124.9 473	22 x 2	358 2309
V951500	480/95R50		164D	TL	W15L	W16L	18.9	479	85.9	2182	39.0	991	256.9	6524	49 1075	67 53	494 224	155.2 588	28.2 x 2	396 2553

TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS VF/SERIES

Item Number	Metric Size	Alt Size	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. vol. gal l	# of lugs	Gross Flat Plate sq in sq cm
							in	mm	in	mm	in	mm	in	mm						
V951517	VF480/95R50		170D	TL	DW16	DW15	19.8	502	85.9	2182	38.7	984	254.5	6464	49 1075	67 53	534 242	156.7 593	28 x 2	586 3782

MAXAM AGRIXTRA 85

MS951R - R1W RADIAL DRIVE TIRE

VF/SERIES

AGRIXTRA 85 LOAD AND INFLATION

Metric Size	Standard Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)																															
				9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	26 psi	27 psi	29 psi	32 psi	35 psi	41 psi	46 psi	55 psi																		
				0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	1.9 bar	2 bar	2.2 bar	2.4 bar	2.8 bar	3.2 bar	3.8 bar																		
250/85R24	9.5R24	109A8/B	5/10 LT	2050/930	2315/1025	2460/1115	2670/1210	2880/1305	3075/1395							3405/1545																			
			25/40 & 30/50		1665/755	1820/825	1975/895	2115/960	2270/1030																										
280/85R24	11.2R24	115A8/B	5/10 LT	2425/1100	2655/1205	2900/1315	3140/1425	3385/1535	3625/1645							4025/1825																			
			25/40 & 30/50		1960/890	2140/970	2325/1055	2500/1135	2680/1215																										
320/85R24	12.4R24	122A8/B	5/10 LT	2985/1355	3285/1490	3585/1625	3880/1760	4180/1895	4485/2035							4960/2250																			
			25/40 & 30/50		2425/1100	2645/1200	2865/1300	3085/1400	3305/1500																										
340/85R24	13.6R24	125A8/B	5/10 LT	3285/1490	3615/1640	3945/1790	4275/1940	4595/2085	4925/2235							5455/2475																			
			25/40 & 30/50		2670/1210	2910/1320	3155/1430	3395/1540	3640/1650																										
380/85R24	14.9R24	131A8/B	5/10 LT	3880/1760	4275/1940	4665/2115	5050/2290	5435/2465	5820/2640							6450/2925																			
			25/40 & 30/50		3155/1430	3440/1560	3725/1690	4010/1820	4300/1950																										
420/85R24	16.9R24	137A8/B	5/10 LT	4585/2080	5040/2285	5500/2495	5950/2700	6415/2910	6865/3115							7605/3450																			
			25/40 & 30/50		3715/1685	4055/1840	4400/1995	4730/2145	5070/2300																										
280/85R28	11.2R28	118A8/B	5/10 LT	2625/1190	2890/1310	3155/1430	3415/1550	3680/1670	3945/1790							4365/1980																			
			25/40 & 30/50		2140/970	2325/1055	2525/1145	2710/1230	2910/1320																										
320/85R28	12.4R28	124A8/B	5/10 LT	3185/1445	3505/1590	3825/1735	4145/1880	4465/2025	4785/2170							5290/2400																			
			25/40 & 30/50		2590/1175	2820/1280	3055/1385	3295/1495	3525/1600																										
340/85R28	13.6R28	127A8/B	5/10 LT	3485/1580	3835/1740	4180/1895	4530/2055	4885/2215	5225/2370							5785/2625																			
			25/40 & 30/50		2835/1285	3085/1400	3340/1515	3605/1635	3860/1750																										
380/85R28	14.9R28	133A8/B	5/10 LT	4100/1860	4510/2045	4925/2235	5335/2420	5745/2605	6150/2790							6810/3090																			
			25/40 & 30/50		3330/1510	3640/1650	3935/1785	4245/1925	4540/2060																										

AGRIXTRA 85 LOAD AND INFLATION

Continued

Metric Size	Standard Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)																																
				9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	26 psi	27 psi	29 psi	32 psi	35 psi	41 psi	46 psi	55 psi																			
				0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	1.9 bar	2 bar	2.2 bar	2.4 bar	2.8 bar	3.2 bar	3.8 bar																			
420/85R28	16.9R28	139A8/B	5/10 LT	4840/2195	5325/2415	5810/2635	6295/2855	6780/3075	7265/3295							8035/3645																				
			25/40 & 30/50		3925/1780	4290/1945	4640/2105	5005/2270	5355/2430																											
380/85R30	14.9R30	135A8/B	5/10 LT	4345/1970	4775/2165	5215/2365	5645/2560	6075/2755	6515/2955							7210/3270																				
			25/40 & 30/50		3525/1600	3845/1745	4165/1890	4485/2035	4805/2180																											
420/85R30	16.9R30	140A8/B	5/10 LT	4980/2260	5480/2485	5975/2710	6470/2935	6965/3160	7475/3390							8265/3750																				
			25/40 & 30/50		4045/1835	4410/2000	4775/2165	5150/2335	5510/2500																											
460/85R30	18.4R30	145A8/B	5/10 LT	5775/2620	6350/2880	6935/3145	7505/3405	8090/3670	8665/3930							9590/4350																				
			25/40 & 30/50		4685/2125	5115/2320	5545/2515	5965/2705	6395/2900																											
320/85R32	12.4R32	126A8/B	5/10 LT	3385/1535	3725/1690	4070/1845	4400/1995	4740/2150	5085/2305							5625/2550																				
			25/40 & 30/50		2745/1245	3000/1360	3250/1475	3495/1585	3750/1700																											
380/85R34	14.9R34	146A8/B	5/10 LT	4585/2080	5040/2285	5500/2495	5955/2700	6415/2910	6870/3115	7400/3355						7915/3590	8445/3830	8965/4065	9925/4500																	
			25/40 & 30/50		3715/1685	4055/1840	4400/1995	4730/2145	5070/2300	5455/2475	5845/2650	6230/2825	6615/3000																							
420/85R34	16.9R34	142A8/B	5/10 LT	5280/2395	5810/2635	6340/2875	6855/3110	7385/3350	7915/3590							8765/3975																				
			25/40 & 30/50		4290/1945	4675/2120	5060/2295	5455/2475	5840/2650																											
460/85R34	18.4R34	147A8/B	5/10 LT	6130/2780	6735/3055	7350/3335	7960/3610	8575/3890	9180/4165							10175/4615																				
			25/40 & 30/50		4970/2255	5425/2460	5875/2665	6325/2870	6780/3075																											
320/85R36	12.4R36	128A8/B	5/10 LT	3585/1625	3945/1790	4300/1950	4665/2115	5015/2275	5380/2440							5950/2700																				
			25/40 & 30/50		2910/1320	3175/1440	3440/1560	3705/1680	3970/1800																											
340/85R36	13.6R36	132A8/B	5/10 LT	3980/1805	4375/1985	4785/2170	5180/2350	5580/2530	5975/2710							6615/3000																				
			25/40 & 30/50		3230/1465	3525/1600	3825/1735	4110/1865	4410/2000																											



MAXAM AGRIXTRA H

MS951R - R1W RADIAL DRIVE TIRE

VF/SERIES

Large volume R1W tires designed specifically for harvesting machines. Premium 45° lug profile provides excellent traction and minimizes vibration while roading. Low pressure and wide footprint lowers soil compaction.

- ▶ Radial tire construction
- ▶ Wide tread for maximized performance in the field
- ▶ Self-cleaning tread design
- ▶ Steel belted for durability
- ▶ Low pressure for minimal soil disturbance
- ▶ Premium rubber compounds reduce ozone cracking and weathering



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



Item Number	Size	Replaces	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. Vol. gal l	# of Lugs	Gross Flat Plate sq in sq cm
							in	mm	in	mm	in	mm	in	mm						
V951137	1000/50R25		172D	TL	36.0TH	W14L	41.7	1059	66.4	1685	28.6	727	198.4	5038	44 800	72 57	807 366	263.5 998	20 x 2	499 3217
V951206	620/75R26	23.1R26	166A8/B	TL	DW20B		24.8	629	62.5	1588	27.3	693	187.2	4754	43 750	66 52	501 227	124.6 472	18 x 2	360 2320
V951502	620/75R30	23.1R30	168D	TL	DW20B		25.2	641	66.8	1696	30.3	770	187.2	4754	44 800	74 59	478 217	147.6 559	20 x 2	433 2791
V951148	750/50R26		157D	TL	DW25B	DW23B	29.8	756	55.5	1410	24.5	623	166	4216	41 675	50 40	346 157	120.9 458	17 x 2	326 2106
V951118	750/65R26	28LR26	166D	TL	DW25B	DW23B	30.1	764	64.4	1636	28	711	192.6	4892	44 775	71 56	598 271	172.4 653	20 x 2	419 2706
V951126	650/75R32	24.5R32	172D	TL	DW21B	DW20B, DW23B	25.8	655	70.4	1789	31	787	210.6	5349	45 875	73 58	593 269	168.2 637	21 x 2	427 2757
V951505	710/75R34		178D	TL	DW23B	MW23B	28.3	719	76.1	1933	33.4	849	230.3	5850	47 925	74 59	681 309	228 863	20 x 2	578 3729
V951121	800/65R32	30.5LR32	178D	TL	DW27B	DW25B, DH27B	30.3	770	73	1853	32	812	218.1	5540	46 875	73 58	761 345	219.1 830	21 x 2	509 3282
V951228	800/70R32		181D	TL	DW27B	DW25B, DH27B	32.3	820	76.3	1937	34.8	884	225.4	5725	47 925	73 58	798 362	256.1 970	21 x 2	633 4085

TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



Item Number	Size	Replaces	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. Vol. gal l	# of Lugs	Gross Flat Plate sq in sq cm
							in	mm	in	mm	in	mm	in	mm						
V951138	900/60R32	35.5LR32	181D	TL	DW27B	DW28B, DW30B	33.5	850	74.5	1893	32.6	828	222.9	5660	47 925	72 57	871 395	257.9 977	21 x 2	560 3611
V951503	1050/50R32		184D	TL	36.00VA	DW36B	41.7	1059	73.5	1863	32.1	816	219.3	5570	46 875	59 47	959 435	318.1 1205	20 x 2	611 3939
V951504	1250/50R32		194A8/B	TL	DH44	DW44B, DH44H, DH44B	49.8	1264	81.1	2059	36	914	237	6020	48 975	76 60	1246 565	379.6 1438	20 x 2	1017 6561

TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS VF/SERIES

Item Number	Size	Replaces	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. Vol. gal l	# of Lugs	Gross Flat Plate sq in sq cm
							in	mm	in	mm	in	mm	in	mm						
V951506	VF500/85R24		163A8	TL	W16L	DW16L	20.9	532	57.6	1463	25.2	641	171.4	4353	41 700	49 39	284 129	113.9 431	20 x 2	403.5 2603

MAXAM AGRIXTRA H

MS951R - R1W RADIAL DRIVE TIRE

VF/SERIES



AGRIXTRA H LOAD AND INFLATION

Metric Size	Standard Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg) <i>continued</i>						
				15 psi	18 psi	20 psi	23 psi	26 psi	29 psi	32 psi
				1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	2 bar	2.2 bar
1000/50R25		172D	5/10 LT	11950/5420	13210/5990	14465/6560	15720/7130	16460/7465	17200/7800	17940/8135
			40/65	8885/4030	9810/4450	10750/4875	11685/5300	12240/5550	12790/5800	13340/6050
			up to 5/10 cyclic	13515/6130	14785/6705	16065/7285	17330/7860	18600/8435	19865/9010	20615/9350
			up to 10/15 cyclic	12325/5590	13485/6115	14640/6640	15800/7165	16955/7690	18115/8215	18800/8525
620/75R26	23.1R26	166A8/B	10 LT	8720/3955	9450/4285	10175/4615	10905/4945	11545/5235	12170/5520	12810/5810
			25/40	6440/2920	6980/3165	7510/3405	8050/3650	8520/3865	8985/4075	9460/4290
			up to 5/10 cyclic	10035/4550	10760/4880	11490/5210	12225/5545	12955/5875	13680/6205	14320/6495
			up to 10/15 cyclic	9150/4150	9810/4450	10475/4750	11145/5055	11810/5355	12480/5660	13055/5920
620/75R30	23.1R30	168D	10 LT	9100/4130	9790/4440	10250/4650	11400/5170	12370/5610	12850/5830	13340/6050
			40/65	6680/3030	7230/3280	7600/3450	8490/3850	9210/4180	9570/4340	9930/4505
			up to 5/10 cyclic	10270/4660	10845/4920	11220/5090	12170/5520	13370/6065	13980/6340	14570/6610
			up to 10/15 cyclic	9370/4250	9890/4485	10230/4640	11090/5030	12190/5530	12740/5780	13280/6025
750/50R26		157D	5/10 LT	7775/3525	8600/3900	9415/4270	10230/4640	10725/4865	11235/5095	11730/5320
			40/65	5775/2620	6395/2900	7000/3175	7605/3450	7980/3620	8355/3790	8720/3955
			up to 5/10 cyclic	8785/3985	9615/4360	10440/4735	11270/5110	12105/5490	12930/5865	13440/6095
			up to 10/15 cyclic	8005/3630	8765/3975	9525/4320	10275/4660	11035/5005	11795/5350	12250/5555
750/65R26	28LR26	166D	5/10 LT	9855/4470	10905/4945	11940/5415	12975/5885	13660/6195	14345/6505	15025/6815
			40/65	7330/3325	8105/3675	8875/4025	9645/4375	10155/4605	10670/4840	11180/5070
			up to 5/10 cyclic	11155/5060	12205/5535	13250/6010	14300/6485	15345/6960	16405/7440	17090/7750
			up to 10/15 cyclic	10165/4610	11125/5045	12085/5480	13045/5915	13990/6345	14950/6780	15590/7070
650/75R32	24.5R32	172D	5/10 LT	10145/4600	11210/5085	12280/5570	13350/6055	14045/6370	14750/6690	15455/7010
			40/65	7540/3420	8335/3780	9130/4140	9925/4500	10450/4740	10970/4975	11500/5215
			up to 5/10 cyclic	11465/5200	12545/5690	13625/6180	14705/6670	15790/7160	16870/7650	17585/7975
			up to 10/15 cyclic	10465/4745	11445/5190	12425/5635	13405/6080	14400/6530	15380/6975	16030/7270
710/75R34		178D	5/10 LT	12565/5700	13350/6055	13880/6295	15190/6890	15850/7190	16500/7485	17815/8080
			40/65	9235/4190	9835/4460	10230/4640	11235/5095	11730/5320	12225/5545	13215/5995
			up to 5/10 cyclic	13800/6260	14725/6680	15335/6955	16865/7650	17635/8000	18400/8345	19930/9040
			up to 10/15 cyclic	12590/5710	13425/6090	13975/6340	15375/6975	16070/7290	16775/7610	18165/8240
800/65R32	30.5LR32	178D	5/10 LT	12280/5570	13570/6155	14875/6745	16165/7330	16790/7615	17420/7900	18060/8190
			40/65	9130/4140	10100/4580	11060/5015	12015/5450	12490/5665	12955/5875	13430/6090
			up to 5/10 cyclic	13880/6295	15190/6890	16505/7485	17805/8075	19115/8670	20430/9265	21070/9555
			up to 10/15 cyclic	12655/5740	13845/6280	15050/6825	16240/7365	17430/7905	18630/8450	19205/8710

AGRIXTRA H LOAD AND INFLATION

Continued

Metric Size	Standard Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)						
				35 psi	38 psi	41 psi	44 psi	46 psi	55 psi	58 psi
				2.4 bar	2.6 bar	2.8 bar	3 bar	3.2 bar	3.8 bar	4.0 bar
1000/50R25		172D	5/10 LT	18685/8475			20835/9450			
			40/65	13890/6300						
			up to 5/10 cyclic	21365/9690	22115/10030	22865/10370	23615/10710			
			up to 10/15 cyclic	19480/8835	20165/9145	20850/9455	21530/9765			
620/75R26	23.1R26	166A8/B	10 LT	13450/6100	14045/6370	14640/6640	15235/6910	15830/7180	17530/7950	
			25/40	9925/4500	10365/4700	10805/4900	11245/5100	11685/5300		
			up to 5/10 cyclic	14960/6785	15590/7070	16230/7360	16870/7650	17465/7920	19270/8740	19865/9010
			up to 10/15 cyclic	13640/6185	14220/6450	14795/6710	15380/6975	15930/7225	17565/7965	18115/8215
620/75R30	23.1R30	168D	10 LT	13990/6345	14640/6640	15280/6930	15610/7080	16580/7520	18520/8400	
			40/65	10410/4725	10910/4950	11390/5165	11620/5270	12300/5600		
			up to 5/10 cyclic	15380/6975	16200/7350	16975/7700	17380/7885	18585/8430	20390/9250	
			up to 10/15 cyclic	14020/6360	14770/6700	15475/7020	15850/7190	16940/7685	18575/8425	
750/50R26		157D	5/10 LT	12240/5550			13650/6190			
			40/65	9095/4125						
			up to 5/10 cyclic	13945/6325	14455/6555	14960/6785	15470/7015			
			up to 10/15 cyclic	12710/5765	13175/5975	13640/6185	14100/6395			
750/65R26	28LR26	166D	5/10 LT	15720/7130			17530/7950			
			40/65	11685/5300						
			up to 5/10 cyclic	17785/8065	18480/8380	19170/8695	19865/9010			
			up to 10/15 cyclic	16220/7355	16845/7640	17485/7930	18115/8215			
650/75R32	24.5R32	172D	5/10 LT	16165/7330	16790/7615	17420/7900	18060/8190	18685/8475	20835/9450	
			40/65	12015/5450	12490/5665	12955/5875	13430/6090	13890/6300		
			up to 5/10 cyclic	18290/8295	19005/8620	19715/8940	20430/9265	21070/9555	22975/10420	23615/10710
			up to 10/15 cyclic	16680/7565	17330/7860	17980/8155	18630/8450	19205/8710	20950/9500	21530/9765
710/75R34		178D	5/10 LT	18685/8475	19555/8870	20435/9270	21485/9745	22180/10060	24800/11250	
			40/65	13880/6295	14540/6595	15210/6900	16005/7260	16500/7500		
			up to 5/10 cyclic	20955/9505	21980/9970	22995/10430	24230/10990	25045/11360	28110/12750	
			up to 10/15 cyclic	19105/8665	20040/9090	20965/9510	22090/10020	22840/10360	25630/11625	
800/65R32	30.5LR32	178D	5/10 LT	18685/8475	19570/8875	20460/9280	21355/9685	22250/10090	24805/11250	
			40/65	13890/6300	14555/6600	15215/6900	15875/7200	16540/7500		
			up to 5/10 cyclic	21710/9845	22335/10130	22975/10420	23615/10710	24520/11120	27210/12340	28115/12750
			up to 10/15 cyclic	19790/8975	20375/9240	20950/9500	21530/9765	22350/10135	24815/11255	25635/11625

*LT = Low Torque

NOTE: Maximum load may not be carried for more than 0.93 miles/1.5km before unloading operation begins. For cyclic hill-side operations over 11° (20%) slope, load adjustments below 20mph/30kmh do not apply.

MAXAM AGRIXTRA H

MS951R - R1W RADIAL DRIVE TIRE

VF/SERIES



AGRIXTRA H LOAD AND INFLATION

Metric Size	Standard Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)						
				15 psi	18 psi	20 psi	23 psi	26 psi	29 psi	32 psi
				1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	2 bar	2.2 bar
800/70R32		181D	5/10 LT	6010/2726	6650/3016	7280/3302	7920/3592	8290/3760	8650/3924	9020/4091
			40/65	9850/4470	10890/4940	11940/5415	12980/5890	13580/6160	14175/6430	14790/6710
			up to 5/10 cyclic	6800/3084	7445/3377	8090/3670	8730/3960	9280/4209	9830/4459	10200/4627
			up to 10/15 cyclic	6200/2812	6790/3080	7370/3343	7960/3611	8460/3837	8960/4064	9300/4218
900/60R32	35.5LR32	181D	5/10 LT	13075/5930	14455/6555	15820/7175	17200/7800	18170/8240	19130/8675	20090/9110
			40/65	9725/4410	10740/4870	11765/5335	12790/5800	13505/6125	14220/6450	14940/6775
			up to 5/10 cyclic	14795/6710	16185/7340	17575/7970	18965/8600	20350/9230	21740/9860	22710/10300
			up to 10/15 cyclic	13485/6115	14750/6690	16020/7265	17285/7840	18555/8415	19825/8990	20715/9395
1050/50R32		184D	5/10 LT	14200/6440	15700/7120	17190/7795	18685/8475	19570/8875	20460/9280	21355/9685
			40/65	10560/4790	11665/5290	12780/5795	13890/6300	14555/6600	15215/6900	15875/7200
			up to 5/10 cyclic	16065/7285	17575/7970	19085/8655	20595/9340	22105/10025	23615/10710	24520/11120
			up to 10/15 cyclic	14650/6645	16030/7270	17410/7895	18775/8515	20155/9140	21530/9765	22350/10135
1250/50R32		194A8/B	10 LT	17780/8065	20215/9170	22310/10120	24745/11225	26145/11860	27535/12490	28585/12965
			25/40	13270/6020	15090/6845	16645/7550	18475/8380	19510/8850	20545/9320	21330/9675
			up to 5/10 cyclic	19350/8770	22010/9980	24280/11010	26950/12225	28460/12910	29970/13595	31115/14110
			up to 10/15 cyclic	17640/8000	20070/9100	22140/10040	24565/11140	25940/11770	27320/12390	28360/12860

AGRIXTRA H LOAD AND INFLATION

VF/SERIES

Metric Size	Standard Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)						
				15 psi	18 psi	20 psi	23 psi	26 psi	29 psi	32 psi
				1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	2 bar	2.2 bar
VF500/85R24		163A8	10 LT	8555/3880	10295/4670	11455/5195	12555/5695	13060/5925	13535/6140	13975/6340
			25/40	6395/2900	7685/3485	8545/3875	9370/4250	9745/4420	10095/4580	10430/4730
			up to 5/10 cyclic	9325/4230	11210/5085	12465/5655	13660/6195	14220/6450	14740/6685	15225/6905
			up to 10/15 cyclic	8500/3855	10220/4635	11365/5155	12455/5650	12965/5880	13435/6095	13880/6295

AGRIXTRA H LOAD AND INFLATION

Continued

Metric Size	Standard Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)						
				35 psi	38 psi	41 psi	44 psi	46 psi	55 psi	58 psi
				2.4 bar	2.6 bar	2.8 bar	3 bar	3.2 bar	3.8 bar	4.0 bar
800/70R32		181D	5/10 LT	9390/4259	9815/4452	10240/4645	10660/4835	24465/11095		
			40/65	15390/6980	16100/7300	16790/7615	17480/7930	18190/8250		
			up to 5/10 cyclic	10560/4790	11050/5012	11540/5234	12015/5450	27475/12460		
			up to 10/15 cyclic	9630/4368	10075/4570	10520/4772	10960/4953	25050/11360		
900/60R32	35.5LR32	181D	5/10 LT	21060/9550	21905/9935	22765/10325	23615/10710	24465/11095	27285/12375	
			40/65	15655/7100	16295/7390	16925/7675	17565/7965	18190/8250		
			up to 5/10 cyclic	23695/10745	24665/11185	25645/11630	26615/12070	27475/12460	30065/13635	30925/14025
			up to 10/15 cyclic	21600/9795	22490/10200	23375/10600	24265/11005	25050/11360	27410/12430	28200/12790
1050/50R32		184D	5/10 LT	22250/10090	23350/10590	24465/11095	25580/11600	26690/12105	29770/13500	
			40/65	16540/7500	17365/7875	18190/8250	19020/8625	19845/9000		
			up to 5/10 cyclic	25415/11525	26315/11935	27210/12340	28115/12750	29240/13260	32610/14790	33735/15300
			up to 10/15 cyclic	23175/10510	23990/10880	24815/11255	25635/11625	26660/12090	29735/13485	30760/13950
1250/50R32		194A8/B	10 LT	29630/13440	31030/14075	32420/14705	33645/15260	34855/15810		
			25/40	22110/10030	23150/10500	24195/10975	25100/11385	26015/11800		
			up to 5/10 cyclic	32250/14630	33770/15320	35290/16005	36610/16600	37950/17215	41700/18915	43140/19570
			up to 10/15 cyclic	29400/13335	30780/13960	32170/14590	33370/15135	34950/15850	38240/17345	39340/17840

AGRIXTRA H LOAD AND INFLATION

Continued

VF/SERIES

Metric Size	Standard Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)						
				35 psi	38 psi	41 psi	44 psi	46 psi	55 psi	58 psi
				2.4 bar	2.6 bar	2.8 bar	3 bar	3.2 bar	3.8 bar	4.0 bar
VF500/85R24		163A8	10 LT	14405/6535						
			25/40	10750/4875						
			up to 5/10 cyclic	15665/7105						
			up to 10/15 cyclic	14285/6480						

NOTE: Maximum load may not be carried for more than 0.93 miles/1.5km before unloading operation begins. For cyclic hill-side operations over 11° (20%) slope, load adjustments below 20mph/30kmh do not apply.

MAXAM AGRIXTRAN

MS951R - R1 & R1W RADIAL DRIVE TIRE VF/SERIES

Narrow tires designed for high load, high traction tractors and sprayers working in row crop applications. Premium 45° lug profile provides excellent traction and minimizes vibration while roading.

- ▶ Radial tire construction
- ▶ Self-cleaning tread design
- ▶ Premium rubber compounds reduce ozone cracking and weathering
- ▶ Wide tread for maximized performance in the field
- ▶ Low pressure for minimal soil disturbance



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



Item Number	Size	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. Vol. gal l	# of Lugs	Gross Flat Plate sq in sq cm
						in	mm	in	mm	in	mm	in	mm						
V951128	420/90R30	147A8/B	TL	DW13	W14L	16.5	418	59.8	1518	26.6	676	178.7	4539	42 725	62 49	265 120	70 265	2 x 20	243 1570
V951509	270/95R32	136D	TL	W9	W7 W8	10.8	275	52.3	1327	24.5	623	160	4055	40 625	44 35	127 57	29.9 113	2 x 24	144 927
V951510	270/95R38	140D	TL	W9	W10 DW10A	10.8	275	58.2	1477	27.7	704.4	177	4505	42 725	44 35	150 68	33.8 128	2 x 26	158 1019
V951508	320/90R46	148A8/B	TL	W10	W10A DW10A	12.6	319	68.7	1744	32.4	823.8	207	5270	45 875	54 43	233 106	50.2 190	2 x 32	195 1261
V951525	340/85R46	150D	TL	W12	W11, DW11, DW12	13.5	343	68.7	1746	32	814	207.5	5270	45 875	54 43	224 102	52.6 199	2 x 28	241 1558
V951114	380/90R46	159A8/B	TL	W12	W11 W13	15	380	72.9	1852	33.5	851	218	5537	46 875	58 46	357 162	77.1 292	2 x 22	237 1532
V951333	420/80R46	151A8/B	TL	W12B	W13B DW13B	15.9	405	72.5	1840	35.5	902	230	5842	46 925	66 52	313 142	88.2 334	2 x 26	286 1844
V951511	230/95R48	136D	TL	W7	W8	9.3	237	65.8	1672	31.3	795	196.8	4999	44 800	42 33	137 62	25.1 95	2 x 32	138 893
V951512	270/95R48	144D	TL	W9	W8 W9 W10	10.8	275	68.2	1733	32.5	824.6	207	5270	45 875	44 35	181 82	39.6 150	2 x 30	176 1135
V951046	380/90R50	160A8/B	TL	W12	W11 W13	15	380	76.9	1954	35.5	902	230	5842	47 975	58 46	386 175	82.6 313	2 x 23	244 1576

TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



Continued

Item Number	Size	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. Vol. gal l	# of Lugs	Gross Flat Plate sq in sq cm
						in	mm	in	mm	in	mm	in	mm						
V951513	300/95R52	151D	TL	W9	W10 W11	12.0	304	74.7	1898	35.2	894.1	228.5	5804	47 975	47 37	234 106	59.2 224	2 x 29	224 1444
V951514	320/90R54	151A8/B	TL	W10	W10A	12.6	319	76.7	1948	36.4	924.3	230	5850	47 975	54 43	264 120	56 212	2 x 36	212 1366
V951515	380/90R54	152A8/B	TL	W12A	W12	15	380	80.9	2056	37.9	962	243	6125	48 1025	62 49	332 151	85 322	2 x 28	296 1910

TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS VF/SERIES

Item Number	Size	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. Vol. gal l	# of Lugs	Gross Flat Plate sq in sq cm
						in	mm	in	mm	in	mm	in	mm						
V951045	VF380/90R46	173D	TL	W13	DW12 DW13	15.1	383	72.9	1852	33.1	842	218	5537	46 925	47 37	342 155	80.8 306	2 x 32	321 2069
V951516	VF380/105R50	179D	TL	W13	DW12 DW13	15.1	383	80.7	2050	36.6	929	241.3	6130	48 1025	53 42	445 202	102 386	2 x 36	382 2467

*LT = Low Torque

MAXAM AGRIXTRAN

MS951R - R1 & R1W RADIAL DRIVE TIRE

VF/SERIES

Narrow tires designed for high load, high traction tractors and sprayers working in row crop applications. Premium 45° lug profile provides excellent traction and minimizes vibration while roading.

- ▶ Radial tire construction
- ▶ Self-cleaning tread design
- ▶ Premium rubber compounds reduce ozone cracking and weathering
- ▶ Wide tread for maximized performance in the field
- ▶ Low pressure for minimal soil disturbance



AGRIXTRAN LOAD AND INFLATION

TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)

Metric Size	LI / SS	Service Speed (mph/kph)	9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	26 psi	29 psi	32 psi	35 psi	38 psi	41 psi	44 psi	46 psi	49 psi	52 psi	58 psi		
			0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	2 bar	2.2 bar	2.4 bar	2.6 bar	2.8 bar	3 bar	3.2 bar	3.4 bar	3.6 bar	4.0 bar		
420/90R30	147A8/B	30 LT/10 HT	4585/2080	5005/2270	5415/2455	5830/2645	6250/2835	6505/2950	6760/3065	7000/3175	7255/3290										
		25/40 & 30/50	4290/1945	4675/2120	5060/2295	5455/2475	5845/2650	6075/2755	6315/2865	6550/2970	6780/3075										
270/95R32	136D	5/10 LT	2360/1070	2735/1240	3130/1420	3485/1580	3900/1770	4290/1945	4575/2075	4730/2145	4870/2210	5025/2280	5315/2410	5465/2480	5765/2615	5910/2680	6085/2760	6260/2840	6620/3000		
		40/65	1760/800	2040/925	2340/1060	2600/1180	2910/1320	3200/1450	3420/1550	3520/1600	3640/1650	3740/1700	3960/1800	4080/1850	4300/1950	4400/2000	4540/2060	4680/2120	4940/2240		
270/95R38	140D	5/10 LT	2590/1175	2955/1340	3395/1540	3900/1770	4290/1945	4730/2145	5025/2280	5170/2345	5315/2410	5465/2480	5765/2615	6085/2760	6260/2840	6435/2920	6790/3080	6965/3160	7385/3350		
		40/65	1930/875	2200/1000	2540/1150	2910/1320	3200/1450	3520/1600	3740/1700	3860/1750	3960/1800	4080/1850	4300/1950	4540/2060	4680/2120	4800/2180	5080/2300	5200/2360	5520/2500		
320/90R46	148A8/B	5/10 LT	3485/1580	4010/1820	4575/2075	5170/2345	5765/2615	6435/2920	6790/3080	6965/3160	7175/3255	7385/3350	7825/3550	8265/3750	8565/3885	8865/4020	9085/4120	9305/4220			
		40/65	2600/1180	3000/1360	3420/1550	3860/1750	4300/1950	4800/2180	5080/2300	5200/2360	5360/2430	5520/2500	5840/2650	6150/2800	6400/2900	6600/3000	6800/3075	6950/3150			
340/85R46	150D	5/10 LT	3660/1660	4255/1930	4850/2200	5545/2515	6140/2785	6735/3055	6995/3175	7420/3365	7640/3465	7815/3545	8310/3775	8610/3905	9145/4150	9305/4220	9685/4390	9900/4490			
		40/65	2760/1250	3200/1450	3640/1650	4080/1850	4540/2060	4940/2240	5200/2360	5520/2500	5680/2575	5840/2650	6180/2805	6425/2915	6800/3085	6945/3150	7200/3265	7385/3350			
380/90R46	159A8/B	5/10 LT	6680/3030	7485/3395	8370/3795	9085/4120	9715/4405	10685/4845	11585/5255	12280/5570	13075/5930	14475/6565									
		25/40 & 30/50	4930/2235	5525/2505	6175/2800	6705/3040	7165/3250	7885/3575	8545/3875	9065/4110	9645/4375										
420/80R46	147A8/B	30 LT/10 HT	5160/2340	5895/2675	6645/3015	7385/3350	8100/3675	8820/4000	9515/4315	10195/4625	10805/4900	11025/5000	11190/5075								
		25/40 & 30/50	3525/1600	4080/1850	4720/2140	5355/2430	5875/2665	6395/2900	6780/3075	7165/3250	7385/3350	7600/3450									
230/95R48	136D	5/10 LT	2290/1040	2735/1240	3040/1380	3485/1580	3900/1770	4290/1945	4430/2010	4575/2075	4870/2210	5025/2280	5170/2345	5465/2480	5610/2545	5910/2680	6085/2760	6260/2840	6620/3000		
		40/65	1710/775	2040/925	2270/1030	2600/1180	2910/1320	3200/1450	3300/1500	3420/1550	3640/1650	3740/1700	3860/1750	4080/1850	4180/1900	4400/2000	4540/2060	4680/2120	4940/2240		

AGRIXTRAN LOAD AND INFLATION

Continued

TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)

Metric Size	LI / SS	Service Speed (mph/kph)	9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	26 psi	29 psi	32 psi	35 psi	38 psi	41 psi	44 psi	46 psi	49 psi	52 psi	58 psi	
			0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	2 bar	2.2 bar	2.4 bar	2.6 bar	2.8 bar	3 bar	3.2 bar	3.4 bar	3.6 bar	4.0 bar	
270/95R48	144D	5/10 LT	2875/1305	3395/1540	3900/1770	4430/2010	4870/2210	5315/2410	5610/2545	5910/2680	6085/2760	6260/2840	6615/3000	6790/3080	7175/3255	7385/3350	7605/3450	7825/3550	8270/3750	
		40/65	2150/975	2540/1150	2910/1320	3300/1500	3640/1650	3960/1800	4180/1900	4400/2000	4540/2060	4680/2120	4940/2240	5080/2300	5360/2430	5520/2500	5680/2575	5840/2650	6150/2800	
380/90R50	160A8/B	5/10 LT	7100/3220	7895/3580	8665/3930	9495/4305	10310/4675	11070/5020	11865/5380	12670/5745	13450/6100	14885/6750								
		25/40 & 30/50	5235/2375	5820/2640	6395/2900	7000/3175	7605/3450	8170/3705	8755/3970	9350/4240	9925/4500									
300/95R52	151D	5/10 LT				4830/2190	5445/2470	6065/2750	6580/2985	6890/3125	7200/3265	7450/3380	7695/3490	8060/3655	8420/3820	8865/4020	9150/4150	9460/4290	9755/4425	10275/4660
		40/65				4300/1950	4440/2015	4585/2080	4805/2180	5025/2280	5245/2380	5455/2475	5675/2575	5930/2690	6175/2800	6425/2915	6670/3025	6925/3140	7165/3250	7605/3450
320/90R54	151A8/B	5/10 LT	3790/1720	4430/2010	5025/2280	5765/2615	6260/2840	6965/3160	7385/3350	7605/3450	7825/3550	8045/3650	8565/3885	8865/4020	9305/4220	9600/4355	9900/4490	10195/4625		
		40/65	2830/1285	3300/1500	3740/1700	4300/1950	4680/2120	5200/2360	5520/2500	5680/2575	5840/2650	6000/2725	6400/2900	6600/3000	6950/3150	7150/3250	7400/3350	7600/3450		
380/90R54	152A8/B	5/10 LT	4870/2210	5765/2615	6435/2920	7385/3350	8045/3650	8865/4020	9305/4220	9900/4490	10195/4625	10485/4755								
		40/65	3640/1650	4300/1950	4800/2180	5520/2500	6000/2725	6600/3000	6950/3150	7400/3350	7600/3450	7850/3550								

AGRIXTRAN LOAD AND INFLATION VF/SERIES

Metric Size	LI / SS	Service Speed (mph/kph)	32 psi	35 psi	38 psi	41 psi	44 psi	46 psi	49 psi	52 psi	55 psi	58 psi	61 psi	64 psi
			2.2 bar	2.4 bar	2.6 bar	2.8 bar	3 bar	3.2 bar	3.4 bar	3.6 bar	3.8 bar	4 bar	4.2 bar	4.4 bar
VF380/90R46	173D	40/65	9800/4445	10210/4630	10630/4820	11040/5005	11450/5195	11860/5380	12270/5565	12690/5755	13100/5940	13520/6130	13920/6315	14330/6500
VF380/105R50	179D	40/65	11685/5300	12170/5520	12670/5745	13165/5970	13660/6195	14145/6415	14630/6635	15125/6860	15610/7080	16120/7310	16605/7530	17100/7750

MAXAM AGRIXTRA XL

MS951R - R1W RADIAL DRIVE TIRE

VF/SERIES

Large volume R1W tires for high horsepower tractor applications. Premium 45° lug profile provides excellent traction and minimizes vibration while roading. Low pressure and wide footprint lowers soil compaction.

- ▶ Radial tire construction
- ▶ Self-cleaning tread design
- ▶ Wide tread for maximized performance in the field
- ▶ Low pressure for minimal soil disturbance
- ▶ Premium rubber compounds reduce ozone cracking and weathering



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



Item Number	Size	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. Vol. gal l	# of Lugs	Gross Flat Plate sq in sq cm
						in	mm	in	mm	in	mm	in	mm						
951120	600/65R28	154D	TL	DW20B	W18L, DW18L	24.1	611	58.7	1491	24.8	629	175.5	4458	42 700	64 51	346 157	124.6 472	19 x 2	297 1915
V951331	600/70R28	161D	TL	DW20B		23.8	605	61.2	1555	27.7	705	183.5	4660	42 725	68 54	392 178	127.2 482	19 x 2	382 2463
V951134	600/70R30	158D	TL	DW20B	W18L, DW18L	24.1	611	63.1	1602	27.9	709	188.6	4790	43 750	71 56	410 186	568 451	20 x 2	336 2170
V951330	650/65R34	161D	TL	DW20B	DW23B	25.6	650	67.3	1710	29.5	750	197	5000	44 775	73 58	487 221	144 545	20 x 2	433 2795
V951501	650/75R38	169D	TL	DW20B		25.4	645	76.4	1941	34.7	880	230	5850	47 925	76 60	588 267	184.9 700	20 x 2	486 3134
V951135	650/85R38	173D	TL	DW23B	DW20B	26.6	676	81.5	2071	36.0	914	243.8	6192	48 975	78 62	767 348	216 818	20 x 2	514 3319
V951123	710/70R38	171D	TL	DW23B		28.2	716	77.1	1959	34.3	870	230.6	5857	47 925	78 62	690 313	211.2 800	20 x 2	487 3140
V951136	800/70R38	178D	TL	DW25B		31.4	798	81.2	2085	36.2	919	245.5	6234	48 975	78 62	908 412	283 1072	21 x 2	594 3830
V951125	710/70R42	173D	TL	DW23B		28.2	716	81.2	2061	36.3	921	242.6	6162	48 975	78 62	754 342	227.3 861	21 x 2	514 3319
V951227	710/75R42	175D	TL	DW23B	DW25B	28.2	716	84	2133	37.4	949	251.1	6378	49 1025	78 62	785 356	252.6 957	22 x 2	546 3523

TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS

VF/SERIES

Continued

Item Number	Size	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. Vol. gal l	# of Lugs	Gross Flat Plate sq in sq cm
						in	mm	in	mm	in	mm	in	mm						
V951528	VF600/65R28	159D	TL	DW21B	DW20B	23.5	597	58.7	1491	24.6	624	176.4	4480	42 700	64 51	356 162	99.6 377	19 x 2	487 3142
V951529	VF600/60R30	158D	TL	DW20B	DW21B	23.5	597	58.3	1482	24.7	628	176.5	4482	42 700	64 51	332 151	93.3 353	20 x 2	461 2975
V951332	VF600/70R30	165D	TL	DW21B	DW20B, DW18L, W18L	23.6	600	63	1600	27.4	695	188.3	4783	43 750	72 57	408 185	123.6 468	20 x 2	387 2497
V951530	VF650/65R34	167D	TL	DW23B	DW21B	25.6	650	67.3	1710	29.5	750	197	5000	44 775	73 58	487 221	144 545	20 x 2	433 2795
V951532	VF710/60R38	171D	TL	DW25B	DW24B, DW27B	27.9	708	71.5	1817	30.6	776	209.1	5310	45 875	73 58	554 252	170.9 647	20 x 2	683 4408
V951535	VF710/60R42	173D	TL	DW25B	DW24B, DW27B	27.9	708	75.6	1919	33	839	229.3	5825	47 925	74 59	605 275	183.9 696	21 x 2	676 4362
V951229	VF710/70R42	179D	TL	DW25B	DW23B	28.7	730	81.9	2080	35.3	896	248.8	6106	48 975	79 63	732 332	229 867	21 x 2	591 3813
V951536	VF710/75R42	181D	TL	DW23B	DW24B	28.4	720	83.3	2115	36.1	917	248.8	6320	49 1025	79 63	783 355	249.6 945	21 x 2	801 5165
V951534	VF650/85R42	180D	TL	DW23B	DW20B, DW21B	25.3	642	85.6	2173	37.2	944	256.6	6517	49 1025	78 62	805 366	235.9 893	21 x 2	787 5076
V951507	VF710/65R46	183D	TL	DW25B		28.1	715	82.5	2095	36.9	938	245	6223	48 1000	76 60	743 337	216.6 820	22 x 2	691 4456

MAXAM AGRIXTRA XL

MS951R - R1W RADIAL DRIVE TIRE

VF/SERIES

Large volume R1W tires for high horsepower tractor applications. Premium 45° lug profile provides excellent traction and minimizes vibration while roading. Low pressure and wide footprint lowers soil compaction.

- ▶ Radial tire construction
- ▶ Self-cleaning tread design
- ▶ Wide tread for maximized performance in the field
- ▶ Low pressure for minimal soil disturbance
- ▶ Premium rubber compounds reduce ozone cracking and weathering



AGRIXTRA XL LOAD AND INFLATION

Metric Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)										
			9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	26 psi	29 psi	32 psi	35 psi	41 psi
			0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	2 bar	2.2 bar	2.4 bar	2.8 bar
600/65R28	154D	5/10 LT	5470/2480	6195/2810	6935/3145	7660/3475	8390/3805	9120/4135	9625/4365	10120/4590	10615/4815	11125/5045	12405/5625
		40/65			5150/2335	5700/2585	6240/2830	6780/3075	7155/3245	7530/3415	7895/3580	8270/3750	
600/70R28	161D	5/10 LT	7060/3200	8030/3640	8950/4060	9810/4450	10430/4730	10950/4970	11500/5215	12040/5460	12390/5620	12730/5775	14270/6475
		40/65			6390/2900	7000/3175	7450/3380	7830/3550	8210/3725	8600/3900	8840/4010	9090/4125	10200/4625
600/70R30	158D	5/10 LT	6315/2865	7155/3245	8005/3630	8840/4010	9690/4395	10530/4775	11045/5010	11565/5245	12085/5480	12600/5715	14055/6375
		40/65			5955/2700	6570/2980	7200/3265	7830/3550	8215/3725	8600/3900	8985/4075	9370/4250	
650/65R34	161D	5/10 LT	7826/3551	9112/4121	10519/4757	11792/5360	12931/5863	13668/6198					
		40/65	5840/2650	6800/3075	7850/3550	8800/4000	9650/4375	10200/4625					
650/75R38	169D	5/10 LT	8040/3652	9313/4221	10519/4757	11792/5360	13266/6030	14338/6533	15276/6901	16080/7303	16482/7504	17152/7772	
		40/65	6000/2725	6950/3150	7850/3550	8800/4000	9900/4500	10700/4875	11400/5150	12000/5450	12300/5600	12800/5800	
650/85R38	173D	5/10 LT	9700/4400	10990/4985	12280/5570	13570/6155	14875/6745	16165/7330	16945/7685	17715/8035	18500/8390	19285/8745	21500/9750
		40/65			9130/4140	10100/4580	11060/5015	12015/5450	12600/5715	13175/5975	13760/6240	14335/6500	
710/70R38	171D	5/10 LT	9425/4275	10685/4845	11950/5420	13210/5990	14465/6560	15720/7130	16350/7415	16980/7700	17605/7985	18235/8270	20340/9225
		40/65			8885/4030	9810/4450	10750/4875	11685/5300	12160/5515	12625/5725	13100/5940	13560/6150	
800/70R38	178D	5/10 LT	11565/5245	13110/5945	14650/6645	16195/7345	17740/8045	19285/8745	20020/9080	20760/9415	21500/9750	22250/10090	24805/11250
		40/65			10895/4940	12040/5460	13185/5980	14335/6500	14885/6750	15435/7000	15985/7250	16540/7500	
710/70R42	173D	5/10 LT	9965/4520	11290/5120	12625/5725	13945/6325	15280/6930	16605/7530	17275/7835	17940/8135	18610/8440	19285/8745	21500/9750
		40/65			9380/4255	10375/4705	11355/5150	12350/5600	12845/5825	13340/6050	13835/6275	14335/6500	
710/75R42	175D	5/10 LT	10670/4840	12105/5490	13530/6135	14950/6780	16370/7425	17795/8070	18465/8375	19130/8675	19800/8980	20460/9280	22820/10350
		40/65			10055/4560	11115/5040	12170/5520	13230/6000	13725/6225	14220/6450	14720/6675	15215/6900	

AGRIXTRA XL LOAD AND INFLATION VF/SERIES

Metric Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)										
			9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	26 psi	29 psi	32 psi	35 psi	41 psi
			0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	2 bar	2.2 bar	2.4 bar	2.8 bar
VF600/65R28	159D	5/10	5940/2695	7005/3180	7955/3610	8910/4045	9765/4430	10610/4815					
		40/65	5400/2450	6370/2890	7230/3280	8100/3675	8875/4025	9645/4375					
VF600/60R30	158D	5/10	5590/2530	7260/3000	7480/3385	8455/3835	9385/4255	10305/4675					
		40/65	5080/2300	6600/2725	6800/3075	7685/3485	8530/3870	9370/4250					
VF600/70R30	165D	5/10	7815/3545	9080/4120	10415/4725	11715/5315	1300/5905	1425/6440					
		40/65	6250/2835	7265/3295	8330/3780	9370/4250	10415/4725	11400/5150					
VF650/65R34	167D	5/10	8215/3725	9790/4440	11365/5155	12400/5625	13440/6100	15000/6815					
		40/65	6570/2980	7830/3550	9090/4125	9920/4500	10750/4880	12000/5450					
VF710/60R38	171D	5/10	8140/3685	9405/4265	10890/4950	12230/5550	13570/6155	14915/6765					
		40/65	7400/3350	8550/3875	9900/4500	11120/5045	12335/5595	13560/6150					
VF710/60R42	173D	5/10	8360/3795	10010/4540	11220/5090	12925/5865	14345/6505	15765/7150					
		40/65	7600/3450	9100/4125	10200/4625	11750/5330	13040/5915	14330/6500					
VF710/70R42	179D	5/10	12300/5575	13865/6290	15425/7000	17200/7800	19150/8690	21375/9690					
		40/65	9840/4460	11090/5030	12340/5600	13760/6240	15320/6950	17100/7750					
VF710/75R42	181D	5/10	12675/5750	14600/6625	16540/7500	18465/8375	20175/9150	22740/10315					
		40/65	10140/4600	11680/5300	13230/6000	14770/6700	16140/7320	18190/8250					
VF650/85R42	180D	5/10	10615/4815	12540/5665	14080/6380	15730/7150	17710/8030	19360/8800					
		40/65	9650/4375	11400/5150	12800/5800	14300/6500	16100/7300	17600/8000					
VF710/65R46	183D	5/10 LT	9975/4525	11670/5295	13370/6065	14855/6740	16345/7415	17610/7990	18705/8485	19740/8955	20540/9318	21215/9625	
		40/65	8855/4018	10560/4790	12155/5515	13500/6125	14855/6740	16015/7265	17030/7727	17945/8140	18675/8473	19290/8750	

*LT = Low Torque